

JT – Series Wall Mount Reverse Osmosis Systems

FLEXEON JT - Series Wall Mount Reverse Osmosis Systems

offer high production capacities and are fully equipped with a computer controller, TDS monitor, multi-stage booster pump, low energy membranes and a sediment filter mounted on a corrosion-resistant, powder-coated aluminum frame.

FLEXEON JT - Series Wall Mount Reverse Osmosis Systems models are available in capacities of 2,000 and 4,000 gallons per day and feature the EZMount™ two-piece wall mounting system for easy installation. An optional mobile stand is also

Leatures

- Minitrol Computer Controller
 - Multi Color LED Indicator Status Light
 - Pre-Treatment Lockout
 - Tank Level Input
 - Low Pressure Monitoring and Alarm
- AXEON HF1 Series Low Energy Membranes
- AXEON PVC Series Membrane Housings
- AXEON 5 Micron Sediment Pre–Filter
- AXEON by Pentek® Big Grey Cartridge Housing
- AXEON Permeate and Concentrate Flow Meters
- AXEON 0 100 psi Pre–Filter Pressure Gauge
- AXEON 0 100 psi Post–Filter Pressure Gauge



- AXEON 0 300 psi Pump Pressure Gauge
- AXEON 0 300 psi Concentrate Pressure Gauge
- Feed Low Pressure Switch
- AXEON by GC Feed Solenoid Valve
- AXEON 316L Stainless Steel Concentrate Valve
- Goulds® Multi-Stage Booster Pump
- John Guest® Push/Pull Fittings with Locking Safety Clips
- White Powder Coated Aluminum Frame

Product Specifications		
Models	JT – 2000	JT – 4000
Design		
Standard Recovery Rate %	31	47
Rejection and Flow Rates		
Nominal Salt Rejection %	99	99
Membranes		
Membrane Quantity	1	2
Membrane Size	4040	4040
Systems Dimensions		
Approximate Dimensions* L x W x H (in / cm)	12 X 48 X 49 / 30.5 X 122.0 X 124.5	12 X 48 X 49 / 30.5 X 122.0 X 124.5
Approximate Weight (lbs / kg)	150 / 68.0	175 / 79.4

^{*} Does not include operating space requirements.

Know Higher Standards



