AXEON

Residential Membrane Housings

AXEON Residential RO Membrane Housings are made from a high-quality, FDA-approved polypropylene.

This component is NSF listed and will accommodate most standard 12" membrane elements.

Both the ribbed cap and the housing are one-piece injection molded parts, requiring no solvents or glues to be used in the manufacturing process. The ribbed cap incorporates acme square threads and two o-rings to ensure a leak-proof seal.

Benefits

- Choice of Single or Dual O-Ring Style
- FDA Grade Materials
- Test Burst Pressure: 400 psi
- Cycle Test: 150,000 Cycles at 150 psi



Specifications

Part Number	200507	208438
Model	2012	3012
Maximum Temperature (°F / °C)	125 / 51.7	125 / 51.7
Maximum Pressure (psi / bar)	80 / 5.5	80 / 5.5
Entry	End, Side, Side, 1 O-Ring	End, Side, Side, 1 O-Ring
Size (in)	0.125 x 0.125 x 0.125	0.375 x 0.375 x 0.375
Case Quantity	24	1
Materials of Construction		
Housing	Reinforced Polypropylene	Reinforced Polypropylene
Finish	Reinforced Polypropylene	Reinforced Polypropylene
O-Ring	EPDM	EPDM





P: 800-320-4074 • W: www.axeonwater.com F: 800-609-0829 • E: sales@axeonwater.com 40980 County Center Drive, Suite 100, Temecula, CA 92591 AXEON is a registered trademark of AXEON Water Technologies.

