

# AQUA FLO

## Aqua Flo Economy Reverse Osmosis System

### Economy Reverse Osmosis Drinking Water System

With the quality of our drinking water increasingly coming under question, people are now looking for alternative sources of quality water. Reverse Osmosis Drinking Water Systems provide the most convenient and economical solution. Neatly stored under the counter, the Reverse Osmosis Drinking Water System provides you with clean and delicious water right from its own dedicated tap.



*“Reverse Osmosis Drinking Water Systems provide the most convenient and economical solution”*



## Features:

- ◆ Heavy duty glass filled polypropylene construction provides double the strength, toughness & durability compared to most other RO's which are typically constructed with ABS.
- ◆ TFC 75 GPD reverse osmosis membrane provides up to 99% Total Dissolved Solids (TDS) rejection
- ◆ Pre-filters 10" five (5) micron Spun Polypropylene Sediment Cartridge and 10" Activated Carbon Cartridge
- ◆ Post filter: 10" Activated Carbon Cartridge
- ◆ Choose from air gap or non-air gap chrome plated faucets
- ◆ 3.0 Gallon NSF Certified plastic storage tank
- ◆ 3/8" outlet tubing for higher flows
- ◆ Automatic shut-off valve
- ◆ Exclusive serviceable check valve eliminates spring 'chatter' noise common in other RO's
- ◆ Quick connect fittings for ease of installation
- ◆ Powder coated bracket
- ◆ Dual purpose wrench for use on membrane cap and filter housing

Model Description	Stages	Sediment Filter	Pre-Filter & Post Filter	Membrane	Rating GPD	Dimensions H x W x D (in)
Aqua Flo Economy 75	4	5 Micron Spun Poly	10 Micron Granular Activated Carbon	TFC	75	14.5 x 15 x 6.1
Aqua Flo Economy 75 BP	4	5 Micron Spun Poly	10 Micron Granular Activated Carbon	TFC	75	17.7 x 15 x 6.9



## Booster Pump Model also includes:

- ◆ Pump mounted on RO to maintain constant water pressure to membrane
- ◆ Raises water pressure to ideal level for maximum efficiency
- ◆ Use on rural supplies with low pressure or high TDS
- ◆ Exclusive Auto Flush feature extends membrane life
- ◆ Self-priming and whisper quiet
- ◆ 24VAC transformer (included) from a standard 120VAC electrical outlet
- ◆ Flexible mounting plate, quick connect fittings and pressure shut-off switch

Feed Water Guidelines	
Maximum TDS	2000 ppm
Hardness	<7gpg
Iron (Fe)	<0.2ppm
Manganese (Mn)	<0.05ppm
Hydrogen Sulfide	0.0ppm
Turbidity	<1.0NTU
Feed Water Pressure	40-100psi
Temperature	40-100°F
pH Range	3.0-11.0
<b>Note:</b> Pretreatment suggested if conditions exceed parameters. Must be installed on potable water.	

# AQUA FLO

A Division of



Your Local Water Specialist