

# **Latest 2-temp Design with Upscale Look**

Newest bottle-less water cooler with integrated cup holder and no-touch, single dispensing faucet provides great tasting hot or cold water at a touch of a button. The built-in filter system provides unlimited supply of fresh great tasting water when you need it eliminating the cost and hassle of 5-gallon bottles.

### **Features**


Two temperature system

Cold: 37-50° F, Adjustable • Hot: 180° F, Autocontrol LED indicator for Hot and Cold water on the front panel

- Newly designed fill opening allows larger cups, mugs or reusable bottles
- Hygienic dispensing touch pad control with no-touch dispensing faucet
- Individual on/off control switches for cold and hot water on rear panel
- Completely sealed stainless steel cold reservoir and hot tank
- Built-in filtration system is easily accessed for replacement
   Available with Reverse Osmosis filtration system

Or Standard Dual-Cartridge filtration system

- Available with ultraviolet or ozone sterilizer
- Attractive LED lighted dispense area
- · Integrated cup dispenser
- 1 year limited warranty
- 3 year compressor warranty



### **Specifications**

Weight: 58 lb.

Dimension: 13"W x 15"D x 42.5"H Cold tank volume 1 gal Hot tank volume .5 gal

Cooling Rate: 1.5 gal/hr 37-50 °F Heating Rate: 1.3 gal/hr 180 °F

Voltage: 115 VAC Power Required: 600w max

Meets Energy Star Requirements ADA compliant

### **Filter System**

Standard Filter 1800F

Stage 1: 5 micron Sediment

Stage 2: 10 micron Activated Carbon

Reverse Osmosis Filter 1800R

Above 2 stages plus

Stage 3: 50-GPD RO Membrane

Automatic tank full control

Fully assembled

- connection hardware included



## **ORDERING INFORMATION**

2-Temp Model - 50 GPD Reverse Osmosis
2-Temp Model - Standard Filtration
2-Temp Dispenser with UV stage
2-temp model with Ozone sanitizer
2-temp Model w/ ProTekk Leak Detector
Replacement Filters Sediment
GAC Carbon

PWC-1800R

PWC-1800R

PWC-1800R

PWC-1800R

PWC-1800R

FWC-1800R

FWC

RO membrane, 75 GPD MA-4203



